



DWG.21

SIZE No. *	DIAMETER OF BODY 'D'		DIAMETER OF HEAD 'A'		HEIGHT OF HEAD 'H'		POINT	
	MAX.	MIN.	MAX.	MIN.	MAX.	MIN.	DIA. Y NOMINAL	LENGTH X NOMINAL
14	0.085	0.079	0.260	0.240	0.042	0.030	0.065	5/64
13	0.097	0.091	0.322	0.302	0.051	0.039	0.073	5/64
12	0.111	0.105	0.353	0.333	0.054	0.040	0.083	5/64
11	0.122	0.116	0.383	0.363	0.059	0.045	0.097	5/64
10	0.136	0.130	0.417	0.395	0.065	0.047	0.109	3/32
9	0.150	0.144	0.448	0.426	0.069	0.051	0.122	3/32
8	0.167	0.161	0.481	0.455	0.072	0.054	0.135	3/32
7	0.183	0.174	0.513	0.487	0.075	0.056	0.151	1/8
6	0.206	0.197	0.606	0.580	0.090	0.068	0.165	1/8
5	0.223	0.214	0.700	0.674	0.105	0.083	0.185	1/8
4	0.241	0.232	0.921	0.893	0.138	0.116	0.204	9/64

All dimensions are given in inches.
 * Size numbers refer to the Stubs iron wire gauge number of stock used in the body of the rivet.
 Length tolerance on rivets shall be plus 1/32inch & minus 0 inch.

BELT RIVETS ARE COMMONLY MADE FROM COPPER. PLEASE SPECIFY MATERIAL WHEN ORDERING

PRODUCT SPECIFICATIONS IN THIS CATALOGUE ARE THOSE IN EFFECT AT THE TIME OF PUBLISHING