



STEEL RIVET/STEEL MANDREL

| TYPE | Part # | LENGTH L | GRIP RANGE G | BODY Ø D | HEAD HEIGHT H | HEAD Ø F | STRENGTH (Kgf) | | Blind Side Protrusion N |
|-----------|-----------|-------------|--------------------|-------------|---------------------|-------------|-------------------|---------|-------------------------------|
| | | | | | | | Shear | Tensile | |
| 4.8 mm | SSA64ML | 10.5 | 1.6-6.9 | 4.8 | 2.2 | 9.2 | 625 | 535 | 19 |
| | SSA67ML | 14.5 | 1.6-11.0 | | | | | | 19 |
| 6.5 mm | SSA86ML | 14.2 | 2.0-9.5 | 6.5 | 2.8 | 13.0 | 1250 | 1000 | 25 |
| | SSA810MLS | 14.2 | 8.9-15.9 | | | | | | 31 |
| | SSA810ML | 14.2 | 2.0-15.9 | | | | | | 36 |

ALUMINIUM RIVET/ALUMINIUM MANDREL

| TYPE | Part # | LENGTH L | GRIP RANGE G | BODY Ø D | HEAD HEIGHT E | HEAD Ø H | STRENGTH (Kgf) | | Blind Side Protrusion N |
|-----------|----------|-------------|--------------------|-------------|---------------------|-------------|-------------------|---------|-------------------------------|
| | | | | | | | Shear | Tensile | |
| 4.8 mm | SAA64ML | 10.5 | 1.6-6.9 | 4.8 | 2.2 | 9.2 | 293 | 263 | 19 |
| | SAA67ML | 14.5 | 1.6-11.0 | | | | | | 19 |
| 6.5 mm | SAA86ML | 14.2 | 2.0-9.5 | 6.5 | 2.8 | 13.0 | 590 | 450 | 25 |
| | SAA810ML | 14.2 | 2.0-15.9 | | | | | | 36 |

STAINLESS RIVET/STAINLESS MANDREL

| TYPE | Part # | LENGTH L | GRIP RANGE G | BODY Ø D | HEAD HEIGHT E | HEAD Ø H | STRENGTH (Kgf) | | Blind Side Protrusion N |
|-----------|-----------|-------------|--------------------|-------------|---------------------|-------------|-------------------|---------|-------------------------------|
| | | | | | | | Shear | Tensile | |
| 4.8 mm | SCCA64ML | 10.5 | 1.6-6.9 | 4.8 | 2.2 | 9.2 | 625 | 500 | 19 |
| | SCCA67ML | 14.5 | 1.6-11.0 | | | | | | 19 |
| 6.5 mm | SCCA86ML | 14.2 | 2.0-9.5 | 6.5 | 2.8 | 13.0 | 1250 | 950 | 25 |
| | SCCA810ML | 14.2 | 2.0-15.9 | | | | | | 36 |

Product specification are in effect at the time of publishing